

Rotulas SA

BRTM30-00-502-DURBAL - BRTM30-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brtm30-00-502-durbal>

BRTM30-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]								
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	b ₁	b ₂	b ₃	
BRTM 30 -00	-502		30	M 30 x 2		34,5	70		37	25
measurements [mm]		weight		rotational speed limit		basic load rating		stat.		
type	h	l	b ₃	α	[°]	[kg]	n _{max}	d _{yn}	C	C ₀
BRTM 30	110	66	35	7,5		0,912	450	32500		24850

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952506814
Diámetro interior	30 mm
Diámetro exterior	70 mm
Espesor	37 mm
Tipo	SA
Peso	912 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE