

Rotulas GE

BRTF20-00-501-DURBAL - BRTF20-00-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/brtf20-00-501-durbal>

BRTF20-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂
BRTF 20 -00	-501		20	27,5	M 20 x 1,5	24,5	50	34	25	18	
		measurements [mm]					weight	rotational speed limit	basic load rating		
type	h	l	l ₁	l ₂	SW	α [°]	[kg]	n _{max} [min ⁻¹]	C [N]	stat. C ₀ [N]	
BRTF 20	77	33	10,0	26	30	7,0	0,361	825	17000	11700	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3616060468185
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	GE
Peso	361 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE