

# Rotulas SI

## BRTF20-00-502-DURBAL - BRTF20-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/brtf20-00-502-durbal>

### BRTF20-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	h <sub>1</sub>	h <sub>2</sub>
BRTF 20 -00		-502	20	27,5	M 20 x 1,5	24,5	50	34	25	18	

type	h	l	l <sub>1</sub>	l <sub>3</sub>	SW	α [°]	weight [kg]	rotational speed limit n <sub>max</sub> [min <sup>-1</sup> ]	basic load rating C [N]	stat. rating C <sub>0</sub> [N]
BRTF 20	77	33	10,0	26	30	7,0	0,361	825	17000	11700

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952506876
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	SI
Peso	361 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE