

Rotulas SI

BRF10-00-501-DURBAL - BRF10-00-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/brf10-00-501-durbal>

BRF10-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

inner ring:
ball bearing steel, hardened, superfinished.

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements (mm)										
type	right-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	h		
BRF 10 -00	-501	10	15,0	M 10	12,0	28	19	14	10,5	43		
measurements (mm)		weight		calculation-factors		rotational speed limit		basic load rating		stat.		
type	l	l ₁	l ₂	SW	α [°]	β [g]	Y	v ₀	C	C ₀	[N]	[N]
BRF 10	20	6,5	15	17	8,0	0,072	1,90	1,81	1225	4450	1450	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507187
Diámetro interior	10 mm
Diámetro exterior	28 mm
Espesor	14 mm
Tipo	SI
Peso	72 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE