


## Rotulas SA

### PM05-00-502-DURBAL - PM05-00-502-DURBAL


https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm05-00-502-durbal

#### PM05-00-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISOA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.
PM 05 -00	-502	5	M 8 x 1	7.5	19	12	12	12	8								
type		l1	l2	l3	h1	h2	u	z	alpha [°]								
PM 05		39,5	13	57	1,5	2,5	7,0	0,037		1,51	1,58	1350	1610	480			

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507439
Diámetro interior	5 mm
Diámetro exterior	19 mm
Espesor	12 mm
Tipo	SA
Peso	37 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE