

Rotulas SA PM05-01-501-DURBAL - PM05-01-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm05-01-501-durbal>

PM05-01-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		type		type		type		type		type		type		type		type		type		type		type	
type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	type	
PM 05 -01	-501	S	M	8 x 1	7,5	19	12	12	12	8													
		measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		dyn.		stat.									
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	Y	γ ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	C ₀ [N]								
PM 05	16	13	33,5	1,5	2,5	7,0			0,033	1,51	1,58	1350	1610	480									

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507453
Diámetro interior	5 mm
Diámetro exterior	19 mm
Espesor	12 mm
Tipo	SA
Peso	33 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE