

Rotulas SA PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm06-02-501-durbal>

PM06-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating				
type	type	d1	d2	d3	d4	d5	d7	b1	b2	l1	l2	l3	u	z	α [°]	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]
PM 06 -02 -501		6	M 10 x 1		8,5	24	14	14	10											
PM 06	19	17	40,5	1,5	2,5	10,5	0,057	1,28	1,34	1300	2445	765								

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507491
Diámetro interior	6 mm
Diámetro interior	0.236" inch
Diámetro exterior	24 mm
Diámetro exterior	0.945" inch
Espesor	14 mm
Espesor	0.551" inch
Tipo	SA
Peso	57 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE