

Rotulas SA PM08-00-502-DURBAL - PM08-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm08-00-502-durbal>

PM08-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating	
type	specification	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]	stat.	dyn.
PM 08 -00	-502	8	M 12 x 1,5	11,0	30	17	15	10					1,9	1,81	1225	2605	985
measurements [mm]		weight		rotational speed limit		basic load rating											
type	l1	l2	l3	h1	h2	u	z	α [°]	α' [°]	weight [kg]	calculation factors	rotational speed limit	basic load rating				
PM 08	46,5	20	72	2,0	2,5	8,5	0,097	1,9	1,81	1225	2605	985					

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507514
Diámetro interior	8 mm
Diámetro exterior	30 mm
Espesor	15 mm
Tipo	SA
Peso	97 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE