

Rotulas SA PM10-00-502-DURBAL - PM10-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm10-00-502-durbal>

PM10-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]			measurements [mm]			
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	l1	l2	l3	
PM 10 -00	-502	10	M 14 x 1,5	13,5	36	19	20	14						
measurements [mm]		weight			rotational speed limit			basic load rating			stat.			
type	l1	l2	l3	h1	h2	u	z	alpha [°]	Y	Yc	nmax [min-1]	C	C0 [N]	C0 [N]
PM 10	49,5	28	82	2,5	2,5	9,5	0,168	1,69	1,77		1100	5120	1905	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507552
Diámetro interior	10 mm
Diámetro exterior	36 mm
Espesor	20 mm
Tipo	-
Peso	168 g
Hilo	-
Lubricación	-
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE