

Rotulas SA

PM10-03-501-DURBAL - PM10-03-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm10-03-501-durbal>

PM10-03-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating	
type	type	d1	d2	d4	d5	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]	stat. [N]
PM 10 -03 -501		10	M 14 x 1,5	12,5	36	1,69	1,77	1100	5120	1905	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507576
Diámetro interior	10 mm
Diámetro exterior	36 mm
Espesor	20 mm
Tipo	SA
Peso	154 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE