

Rotulas SA

PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm15-02-501-durbal>

PM15-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			weight		calculation factors		rotational speed limit		basic load rating	
type	sp. thread	d ₁	d ₂	d ₃	d ₄	d ₅	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	stat. [N]
PM 15 -02	-501	15	M 20 x 1.5	18.5	42	26	2.07	2.17	975	5485	3270	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507651
Diámetro interior	15 mm
Diámetro exterior	42 mm
Espesor	20 mm
Tipo	SA
Peso	273 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE