

Rotulas SA PM17-00-501-DURBAL - PM17-00-501-DURBAL


<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm17-00-501-durbal>

PM17-00-501



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]				measurements [mm]				weight		rotational		basic load rating			
type	sp. h. x t. x d. x r.	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]		
PM 17 -00	-501	17	M 20 x 1,5	21,0	48	25	22	16									
measurements [mm]		weight		rotational		basic load rating											
type	l1	l2	l3	h1	h2	u	z	α [°]	weight [kg]	calculation factors	rotational speed limit	basic load rating					
PM 17	62,5	36	105	3,5	2,5	7,0	0,401		2,35	2,46	875	5575	2680				

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507668
Diámetro interior	17 mm
Diámetro exterior	48 mm
Espesor	22 mm
Tipo	SA
Peso	401 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE