

Rotulas SA

PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm17-01-502-durbal>

PM17-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating					
type	type	d1	d2	d4	d5	d7	b1	b2	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]		
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16							
measurements [mm]		weight		rotational speed limit		basic load rating									
type	l1	l2	l3	h1	h2	u	z	alpha [°]	alpha prime [°]	weight [kg]	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]
PM 17	36	36	78,5	3,5	2,5	7,0				0,354	2,35	2,46	875	5575	2680

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507682
Diámetro interior	17 mm
Diámetro exterior	48 mm
Espesor	22 mm
Tipo	SA
Peso	354 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE