

## Rotulas SA PM20-00-501-DURBAL - PM20-00-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/pm20-00-501-durbal>

### PM20-00-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/AH1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating	
type	type	d1	d2	d4	d5	d7	b1	b2	Y	Yc	nmax [min-1]	C	C0
PM 20 -00	-501	20	M 24 x 1.5	24.0	56	30	24	18					
type		l1	l2	l3	h1	h2	u	z	alpha [°]				
PM 20		68,5	41	117	3,5	3,0	5,5						

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507705
Diámetro interior	20 mm
Diámetro interior	0.787" inch
Diámetro exterior	56 mm
Diámetro exterior	2.205" inch
Espesor	24 mm
Espesor	0.945" inch
Tipo	SA
Peso	587 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE