

Rotulas SA

BRM10-60-501-DURBAL - BRM10-60-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brm10-60-501-durbal>

BRM10-60-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread


inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3402 D10k (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]							
type	197 functional M1 hard thread	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h	
BRM 10 -60	-501	10	M 10	12,0	28	14	10,5	48	
measurements [mm]		weight		calculation factors	rotational speed limit	basic load rating			
type	l	l ₃	α [°]	[kg]	Y ₀	lim. [min.]	C ₀ [N]	stat. C ₀ [N]	
BRM 10	29	15	8,0	0,060	1,90	1,81	1225	3100	1000

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952509129
Diámetro interior	10 mm
Diámetro exterior	28 mm
Espesor	14 mm
Tipo	-
Peso	60 g
Hilo	-
Lubricación	-
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE