Rotulas SA
BRM16-60-502-DURBAL - BRM16-60-502-DURBAL

https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brm16-60-502-durbal



BRM16-60-502

DURBAL

male thread; long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing: stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring: stainless steel, hardened, surface superfinished

lubrication: aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting: DIN 3405 D1/A (sizes 6 to 10) DIN 71 412 H1 (sizes 12 to 20)

bearing clearance: 10 - 30 µm radial

tolerances: see page 10

order number type	right hand thread	left hand thread	d_1	d_3	d_4	d_6	b_1	b_3	h
BRM 16 -60		-502	16	M 16	19,0	42	21	15,0	66

type	l	l_3	α [°]	weight [kg]	Y	Y_0	n_{max} [min⁻¹]	C [N]	C_0 [N]
BRM 16	40	22	8,0	0,190	2,24	2,35	975	4250	1600

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952509174
Diámetro interior	16 mm
Diámetro exterior	42 mm
Espesor	21 mm
Tipo	SA
Peso	190 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es
911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE