

Rotulas SA

BRM20-60-501-DURBAL - BRM20-60-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brm20-60-501-durbal>

BRM20-60-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread


inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 2402 D10k (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]							
type	type	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h	
BRM 20 -60 -501		20	M 20 x 1,5	24,5	50	25	18,0	78	
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating	
type	l	l ₂	α [°]	W [kg]	Y	v _c	C _r [N]	C ₀ [N]	stat. C ₀ [N]
BRM 20	47	28	7,0	0,338	2,46	2,58	825	5350	2300

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952509198
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	SA
Peso	338 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE