


Rotulas SI

BRF16-60-501-DURBAL - BRF16-60-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/brf16-60-501-durbal>

BRF16-60-501 

rod end housing:
stainless steel 1.4534, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished


lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel



female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number		measurements [mm]												
type	light load thread	light load thread	light load thread											
BRF 16 -60 -501		d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	b ₃	h		
		16	22,0	M 16	19,0	42	27	21	15,0	64				
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.				
type	l	l ₁	l ₂	SW	α [°]	Y	λ	n _{max} [min ⁻¹]	C [N]	C ₁₀ [N]	C ₁₀₆ [N]			
BRF 16	28	8,0	22	22	8,0	0,224	2,24	2,35	975	4250	1600			

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952509280
Diámetro interior	16 mm
Diámetro exterior	42 mm
Espesor	21 mm
Tipo	SI
Peso	224 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE