

Rotulas SI

BRTF1-1-00-501-DURBAL - BRTF1-1-00-501-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/brtf1-1-00-501-durbal>

BRTF1/1-00-501



red end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1


lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, dimensions in inches




order number		measurements [inches]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂
BRTF 1/1	-00	-501	1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866	
		measurements [inches]									
type	h	l	l ₁	l ₂	SW	α	weight	rotational speed limit	basic load rating	stat.	stat.
BRTF 1/1	3.720	1.653	.236	1.279	1.181	5,0	0,568	600	24900	18500	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952510071
Diámetro interior	25.4 mm
Diámetro interior	1" inch
Diámetro exterior	63.98 mm
Diámetro exterior	2.519" inch
Espesor	30.99 mm
Espesor	1.22" inch
Tipo	SI
Peso	568 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE