


## Rueda libre FCS-6-NADELLA - FCS-6-NADELLA

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/rueda-libre/fcs-6-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F <sub>6</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
6	FCS-6	6	10	12	2.15	22000	HK0608

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
6	9.984	5.980	6.004	14	6.000	5.995	9.993	9.984	0.003

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NADELLA
Nº Ean13	3663952529370
Diámetro interior	6 mm
Diámetro exterior	10 mm
Espesor	12 mm
Peso	3 g
Envasado	-
Estándar	Ninguna norma

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE