


Casquillos de agujas FCS-35-NADELLA - FCS-35-NADELLA

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/fcs-35-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _o mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
35	FCS-35	35	42	20	107.0	6100	HK3512

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
35	41.972	34.964	35.009	56	Max. 35.000	Min. 34.989	Max. 41.988	Min. 41.972	0.048

CARACTERÍSTICAS DEL PRODUCTO

Marca	NADELLA
Nº Ean13	3663952529509
Diámetro interior	35 mm
Diámetro exterior	42 mm
Espesor	20 mm
Peso	48 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE