

Rueda libre FCB-20-NADELLA - FCB-20-NADELLA

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/rueda-libre/fcb-20-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page.
Types **FCB** and **FCBL** clutch and bearing assemblies have stainless steel springs inserted in the molded cage to position rollers for instantaneous lockup.



Shaft Ø mm	Designation	F _e mm	D mm	C mm	Torque Nm	Load ratings ¹⁾		Overrun limiting speed rating for rotating shaft min ⁻¹
						Dynamic C _d kN	Static C _s kN	
20	FCB-20	20	26	26	32.6	8.16	9.46	11000

Shaft Ø mm	Gaging				Z Minimum outer diameter of steel housing for Torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun and bearing go plug mm	Bearing no go plug mm		Mounting		Mounting		
	Max. mm	Min. mm	Max. mm	Min. mm		Max. mm	Min. mm	Max. mm	Min. mm	
20	25.976	19.970	20.007	20.043	38	20.000	19.991	25.989	25.976	0.028

CARACTERÍSTICAS DEL PRODUCTO

Marca	NADELLA
N° Ean13	3663952529585
Diámetro interior	20 mm
Diámetro interior	0.787" inch
Diámetro exterior	26 mm
Diámetro exterior	1.024" inch
Espesor	26 mm
Espesor	1.024" inch
Peso	28 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE