


## Otros rodamientos ARNB90180-NADELLA - ARNB90180-NADELLA

<https://www.123rodamiento.es/rodamiento-cojinete/otros-rodamientos/arnb90180-nadella>

Precision combined bearings,  
with adjustable axial preload



AXNB and ARNB series



| Shaft<br>d<br>mm | Designation |                  |                  |                  | d<br>mm | D<br>mm | F <sub>w</sub><br>mm | D <sub>a</sub><br>mm | D <sub>m</sub><br>mm | B<br>mm | C<br>mm | B <sub>1</sub><br>mm | r<br>min. | f <sub>1</sub><br>min. |
|------------------|-------------|------------------|------------------|------------------|---------|---------|----------------------|----------------------|----------------------|---------|---------|----------------------|-----------|------------------------|
|                  | AXNB        | ARNB<br>series 1 | ARNB<br>series 2 | ARNB<br>series 3 |         |         |                      |                      |                      |         |         |                      |           |                        |
| 90               |             |                  |                  | 90 180           | 90      | 180     | 110                  | 180                  | 132.9                | 110     | 35      | 37.5                 | 1.75      | 0.85                   |

| Load Ratings kN |          |        |          | Speed<br>rating<br>min <sup>-1</sup> | Preload <sup>1)</sup><br>N | Rotation <sup>2)</sup><br>torque<br>Nmm | Rigidity K <sup>3)</sup><br>N/mm | Weight<br>kg | Designation |
|-----------------|----------|--------|----------|--------------------------------------|----------------------------|---|----------------------------------|--------------|-------------|
| radial          |          | axial  |          |                                      |                            |   |                                  |              |             |
| Dyn. C          | Stat. Co | Dyn. C | Stat. Co |                                      |                            |   |                                  |              |             |
| 118.0           | 268.0    | 268.0  | 990.0    | 1.900                                | 17.640                     | 22.200                                  | 3.700                            | 11.654       | ARNB 90 180 |

1) 6% of dynamic axial load - 2) with axial load equal to preload - 3) rigidity of a single thrust bearing with load equal to preload

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | NADELLA       |
| Nº Ean13          | 3663952530680 |
| Diámetro interior | 90 mm         |
| Diámetro exterior | 160 mm        |
| Espesor           | 110 mm        |
| Peso              | 11654 g       |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE