

## Casquillos de agujas TJ7214-RBC - TJ7214-RBC

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/tj7214-rbc>

# Heavy Duty TJ TandemRoller® Bearings

TJ TandemRoller® Bearing

| BEARING<br>PART<br>NUMBER | Pw<br>Inside Diameter |        |        | D<br>Outside Diameter |        | B<br>Width<br>+0.00<br>-0.00 | r <sub>1</sub><br>Housing<br>Fillet<br>Max | Housing<br>Shoulder<br>Dia.<br>+/- 1/64" | Dynamic<br>Capacity<br>C (lbs.) | Static<br>Capacity<br>C <sub>0</sub> (lbs.) |
|---------------------------|-----------------------|--------|--------|-----------------------|--------|------------------------------|--------------------------------------------|------------------------------------------|---------------------------------|---------------------------------------------|
|                           | Nominal               | Min.   | Max.   | Min.                  | Max.   |                              |                                            |                                          |                                 |                                             |
| TJ 7214                   | 1.18                  | 1.1259 | 1.1268 | 1.525                 | 1.6245 | 1.000                        | .040                                       | 1.3/8                                    | 8,500                           | 15,500                                      |

| Limit<br>Speed<br>(rpm) | Recommended Shaft Diameter     |        |                                |        | Recommended Housing Bore |          |                  |        | BEARING<br>PART<br>NUMBER |        |
|-------------------------|--------------------------------|--------|--------------------------------|--------|--------------------------|----------|------------------|--------|---------------------------|--------|
|                         | ISO H6, use with<br>N7 sag fit |        | ISO R6, use with<br>N7 hog fit |        | Slip Fit ISO H7          |          | Press Fit ISO N7 |        |                           |        |
|                         | Max.                           | Min.   | Max.                           | Min.   | Max.                     | Mean Fit | Min.             | Max.   | Mean Fit                  |        |
| 10,500                  | 1.1290                         | 1.1245 | 1.1242                         | 1.1237 | 1.6250                   | 1.6280   | .0007L           | 1.6237 | 1.6247                    | .0006T |

All dimensions in inches.

1) Prefix DTJ denotes a double row bearing.

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | RBC           |
| Nº Ean13          | 3663952533490 |
| Diámetro interior | 28.575 mm     |
| Diámetro exterior | 41.275 mm     |
| Espesor           | 25.4 mm       |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE