

Rodamiento de bolas una hilera 1602-DS-NICE - 1602-DS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1602-ds-nice>

1600 Series™ Precision Ground Radial Bearings NICE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
1602™					DS	0.2500 6.350	0.6875 17.463
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (lb) (g)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.2500 6.350	511 2274	170 757	0.02 0.01	0.330 8.38	0.614 15.60	0.012 0.30	

Width for sealed versions = 0.3125 (7.938) Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952556949
Diámetro interior	6.35 mm
Diámetro exterior	17.463 mm
Espesor	6.35 mm
Peso	10 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE