







## Rodamiento de bolas una hilera 1607-NS-NICE - 1607-NS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1607-ns-nice>

**1600** Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE <b>d</b> (in) (mm)	O.D. <b>D</b> (in) (mm)
						+0.000 +0.00 -0.0005 -0.013	+0.000 +0.00 -0.0005 -0.013
1607™					NS	0.4375 11.113	0.9003 23.000
WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
<b>B</b> (in) (mm)	<b>C</b> (lb) (N)	<b>C<sub>0</sub></b> (lb) (N)	<b>W<sup>0</sup></b> (lb) (g)	<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)	
+0.000 +0.00 -0.005 -0.13	698 3106	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38	

Weights given are for greased and sealed versions

### CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952557175
Diámetro interior	11.113 mm
Diámetro exterior	23.02 mm
Espesor	7.938 mm
Peso	10 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE