


Rodamiento de bolas una hilera 1615-NS-NICE - 1615-NS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1615-ns-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.0005 -0.013
1615™					NS	0.4375 11.113	1.1250 28.575
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (lb) (g)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.3750 9.525	1200 5340	475 2114	0.08 0.03	0.822 15.80	1.014 25.76	0.025 0.64	

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952557250
Diámetro interior	11.113 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE