

Rodamiento de bolas una hilera 1628-DS-NICE - 1628-DS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1628-ds-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
1628™			DS			0.9250 15.875	1.8250 41.275
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.5000 12.700	2595 11548	1010 4495	0.18 0.08	0.845 21.46	1.446 36.73	0.025 0.64	

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952557526
Diámetro interior	15.875 mm
Diámetro exterior	41.275 mm
Espesor	12.7 mm
Peso	80 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE