

Rodamiento de bolas una hilera 1641-SS-NICE - 1641-SS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1641-ss-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
1641™					SS	1.9000 25.400	2.0000 50.800
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.5625 14.288	2967 13203	1350 6008	0.26 0.12	1.197 30.40	1.780 44.70	0.035 0.89	

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952557830
Diámetro interior	25.4 mm
Diámetro exterior	50.8 mm
Espesor	14.288 mm
Peso	120 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE