

## Rodamiento de bolas una hilera 1652-SC-NICE - 1652-SC-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/1652-sc-nice>

**1600** Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
1652™		SC				+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
						1.1250 28.575	2.3000 63.500

  

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.6250 15.875	3864 17195	2120 9434	0.38 0.17	1.375 34.93	2.244 57.00	0.035 0.89

Weights given are for greased and sealed versions

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952557885
Diámetro interior	28.575 mm
Diámetro exterior	63.5 mm
Espesor	15.875 mm
Peso	170 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE