




Rodamiento de bolas una hilera 3004-DS-NICE - 3004-DS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3004-ds-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3004™			DS			+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 Ⓞ -0.015
						0.3750 9.525	0.8750 22.225

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
0.2813 Ⓞ 7.1450	325 1448	255 1135	0.03 0.01	0.474 12.04	0.778 19.78	0.015 0.38	

Ⓞ Width for sealed versions = 0.3438 (8.733)
Ⓞ Weights given are for greased and sealed versions
Ⓞ 3038 and larger +0.0005/-0.006 (-0.001/-0.15)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558127
Diámetro interior	9.525 mm
Diámetro exterior	22.225 mm
Espesor	7.145 mm
Peso	10 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE