



Rodamiento de bolas una hilera 3005-SC-NICE - 3005-SC-NICE






<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3005-sc-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

NICE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING						BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.013 -0.013
3005™		SC				0.3125 7.938	0.9063 23.020

BASIC LOAD RATINGS		WEIGHT		ABUTMENT AND FILLET DIMENSIONS		
DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lbs) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
350 1568	300 1355	0.04 0.02	0.503 12.76	0.778 19.76	0.012 0.30	

Ⓢ Weights given are for greased and sealed versions
 Ⓞ 3038 and larger +.0000/-0.005 (-.000/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558165
Diámetro interior	7.938 mm
Diámetro exterior	23.02 mm
Espesor	7.938 mm
Peso	20 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE