

Rodamiento de bolas una hilera 3007-SC-NICE - 3007-SC-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3007-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3007™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.013 0.0063
						11.113	23.020

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
0.3125 7.938	300 1508	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38	

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558264
Diámetro interior	11.113 mm
Diámetro interior	7/16" inch
Diámetro exterior	23.02 mm
Diámetro exterior	29/32" inch
Espesor	7.938 mm
Espesor	5/16" inch
Peso	10 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE