



Rodamiento de bolas una hilera 3015-SS-NICE - 3015-SS-NICE






<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3015-ss-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

NICE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
3015™				SS		0.4375 11.113	1.1250 28.575

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	C (lbs) (N)	Co (lbs) (N)	W (lbs) (kg)	d_a min (in) (mm)	D_a max (in) (mm)	r max (in) (mm)	
+0.005 +0.00 -0.005 -0.13	600 2670	475 2114	0.06 0.03	0.622 15.80	1.014 25.76	0.025 0.64	

Ⓞ Weights given are for greased and sealed versions
 Ⓞ 3015 and larger +0.0005/-0.005 (+0.001/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558387
Diámetro interior	11.113 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE