

Rodamiento de bolas una hilera 3016-DC-NICE - 3016-DC-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3016-dc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3016™ | DC | | | | | +0.005 +0.13 -0.00 -0.013 | +0.000 +0.00 -0.0005 -0.013 |

| BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|-------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | W O (lbs) (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.3750 9.525 | 600 2670 | 475 2114 | 0.06 0.03 | 0.622 15.80 | 1.014 25.76 |

Ⓞ Weights given are for greased and sealed versions
Ⓞ 3016 and larger +0.000/-0.005 (+0.00/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | NICE |
| N° Ean13 | 3663952558448 |
| Diámetro interior | 12.7 mm |
| Diámetro interior | 1/2" inch |
| Diámetro exterior | 28.575 mm |
| Diámetro exterior | 1 1/8" inch |
| Espesor | 9.525 mm |
| Espesor | 3/8" inch |
| Peso | 30 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE