


Rodamiento de bolas una hilera 3030-SS-NICE - 3030-SS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3030-ss-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3030™				SS		+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 Ⓞ
						0.7500 19.050	1.5250 41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1010 4485	0.16 0.07	0.965 24.51	1.446 36.73	0.025 0.64

Ⓞ Weights given are for greased and sealed versions
Ⓞ 3030 and larger +0.0005/-0.0005 (+0.001/-0.125)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558684
Diámetro interior	19.05 mm
Diámetro interior	3/4" inch
Diámetro exterior	41.275 mm
Diámetro exterior	1 5/8" inch
Espesor	12.7 mm
Espesor	1/2" inch
Peso	70 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE