


Rodamiento de bolas una hilera 3033-SS-NICE - 3033-SS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3033-ss-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|-------------------------------------|---|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3033™ | | | | SS | | +0.005 +0.13 -0.000 -0.013 | +0.000 +0.00 -0.0005 O -0.013 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|-----------------------------|------------------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC Co (lb) (N) | W O (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.5000 12.700 | 1300 5785 | 1025 4561 | 0.22 0.10 | 0.845 21.46 | 1.530 38.86 | 0.025 0.64 |

O Weights given are for greased and sealed versions
 O 3038 and larger +0.0005/-0.005 (+0.001/-0.125)

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | NICE |
| N° Ean13 | 3663952558714 |
| Diámetro interior | 15.875 mm |
| Diámetro exterior | 44.45 mm |
| Espesor | 12.7 mm |
| Peso | 100 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE