


Rodamiento de bolas una hilera 3033-DC-NICE - 3033-DC-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3033-dc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3033™	DC					+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005 O -0.013
						0.6250 15.875	1.7000 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W O (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1025 4561	0.22 0.10	0.845 21.46	1.530 38.86	0.025 0.64

O Weights given are for greased and sealed versions
 O 3033 and larger +0.0005/-0.005 (+0.001/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558745
Diámetro interior	15.875 mm
Diámetro exterior	44.45 mm
Espesor	12.7 mm
Peso	100 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE