


Rodamiento de bolas una hilera 3038-DS-NICE - 3038-DS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3038-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3038™			DS			+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005 -0.013
						0.7500 19.050	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W ^⓪ (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.9625 14.288	1480 6588	1350 6008	0.32 0.15	0.988 25.10	1.760 44.70	0.035 0.89

^⓪ Weights given are for greased and sealed versions
^⓪ 3038 and larger +.0000/-0.0005 (+.000/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558820
Diámetro interior	19.05 mm
Diámetro exterior	50.8 mm
Espesor	14.288 mm
Peso	150 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE