

## Rodamiento de bolas una hilera 3038-DS-NICE - 3038-DS-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/3038-ds-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3038™			DS			+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 $\text{O}$ -0.013
						0.7500 19.050	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W $\text{O}$ (lb) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6588	1350 6008	0.32 0.15	0.988 25.10	1.760 44.70	0.035 0.89

$\text{O}$  Weights given are for greased and sealed versions  
 $\text{O}$  3038 and larger +0.0005/-0.005 (+0.001/-0.13)

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558820
Diámetro interior	19.05 mm
Diámetro exterior	50.8 mm
Espesor	14.288 mm
Peso	150 g
Envasado	-

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE