


## Rodamiento de bolas una hilera 400-5V-NICE - 400-5V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/400-5v-nice>

**400 Series® Single Row Unground Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	5V	0.312 7.92 +0.0005-0.0007 -13/-00	0.875 22.23 +0.005-0.000 -13/-00	0.250 6.35 +0.010-0.010 -25/-20	0.250 6.35 Reference	14	1/8 3-18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.03	196	108	75	60	42	30
0.01	694	481	334	267	187	134

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952559988
Diámetro interior	7.92 mm
Diámetro exterior	22.23 mm
Espesor	6.35 mm
Peso	10 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE