


Rodamiento de bolas una hilera 400-6V-NICE - 400-6V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/400-6v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	6V	0.375 +0.0005-0.000 9.27	0.875 +0.005-0.000 22.23	0.250 +0.010-0.010 6.35	0.250 Reference 6.35	14	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.03	156	108	75	60	42	30
0.01	694	481	334	267	187	134

Notes
Balls - Carbon Steel Grade 200
Rings - Carbon Steel, Case Hardened
Balls - 1010 Carbon Steel, Soft
Bearings supplied prelubricated with grease

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952559995
Diámetro interior	9.53 mm
Diámetro exterior	22.23 mm
Espesor	6.35 mm
Peso	10 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE