


## Rodamiento de bolas una hilera 400-12V-NICE - 400-12V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/400-12v-nice>

**400 Series® Single Row Unground Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	12V	0.375 9.53 +0.0005-0.0008 -0.13-0.00	0.397 10.08 +0.0005-0.0008 -0.13-0.00	0.312 7.92 +0.010-0.010 -0.25-0.25	0.312 7.92 Reference	15	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.04 0.02	167 743	116 516	80 356	65 288	45 200	32 142

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952560007
Diámetro interior	9.53 mm
Diámetro exterior	23.8 mm
Espesor	7.92 mm
Peso	20 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE