


Rodamiento de bolas una hilera 400-20V-NICE - 400-20V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/400-20v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA					
		A	B	C	D	BALLS	
		BORE (in) (mm)	O.D. (in) (mm)	WIDTH (in) (mm)	WIDTH (in) (mm)	No.	Size
400™	20V	0.375 9.53 +0.0005-0.0008 -0.131-0.00	1.125 28.58 +0.0050-0.0008 -0.131-0.00	0.375 9.53 +0.0110-0.0110 -0.251-0.25	0.375 9.53 Reference	18	18 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.08 0.04	200 890	139 619	96 427	78 347	54 243	38 168

Notes
Balls - Carbon Steel Grade 200
Rings - Carbon Steel, Case Hardened
Bands - 1010 Carbon Steel, Soft
Bearings supplied prelubricated with grease

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952560045
Diámetro interior	9.53 mm
Diámetro exterior	28.58 mm
Espesor	9.53 mm
Peso	40 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE