


Rodamiento de bolas una hilera 400-47V-NICE - 400-47V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/400-47v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	47V	1.250 31.75 +0.000/-0.005	2.625 66.68 +0.035/0.000	0.687 17.45 +0.010/-0.010	0.687 17.45 Reference	23	1/4 6.35

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
	(N)	(N)	(N)	(N)	(N)	(N)
0.75	1020	710	490	395	275	193
0.34	4559	3160	2181	1758	1224	859

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560175
Diámetro interior	31.75 mm
Diámetro exterior	66.68 mm
Espesor	17.45 mm
Peso	340 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE