


Rodamiento de bolas una hilera 5507-V-NICE - 5507-V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/5507-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5507™	V	0.312 7.92	1.149 28.98	0.385 9.78	0.062 1.57	1.250 31.75	0.125 3.18	0.437 11.10

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
15	5/32 3.97	300 800	139 819	96 427	78 347	54 240	33 169

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560236
Diámetro interior	7.92 mm
Diámetro interior	0.312" inch
Diámetro exterior	28.58 mm
Diámetro exterior	1 1/8" inch
2º Diámetro exterior	31.75 mm
2º Diámetro exterior	1 1/4" inch
Espesor	9.78 mm
Espesor	0.385" inch
2º Espesor	11.1 mm
2º Espesor	0.437" inch
Peso	40 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE