


Rodamiento de bolas una hilera 5281-V-NICE - 5281-V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/5281-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5281™	V	0.500 12.70 +0.005/-0.000 +13/-00	1.539 40.08 +0.005/-0.000 +18/-00	0.515 13.08 +0.010/-0.010 +25/-25	0.140 3.56	1.887 42.85	0.234 5.94	0.809 15.47 +0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (%)	100 (lbs) (%)	200 (lbs) (%)	300 (lbs) (%)	600 (lbs) (%)	1200 (lbs) (%)	
12	1/4 6.35	0.23 0.10	535 2381	367 1633	258 1148	206 917	144 641	100 445

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560298
Diámetro interior	12.7 mm
Diámetro exterior	40.08 mm
2º Diámetro exterior	42.85 mm
Espesor	13.08 mm
2º Espesor	15.47 mm
Peso	100 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE