


Rodamiento de bolas una hilera 602-V-NICE - 602-V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/602-v-nice>

600 Series™ Unground Thrust Bearings **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIXED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in)	BORE (in)	O.D. (in)	HEIGHT (in)		
602™	V	.375 9.53	+.010 10.15	1.384 26.59	-.359 9.12	14 5/32 3.97	0.06 0.03

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10	50	100	250	500	1000
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
(N)	(N)	(N)	(N)	(N)	(N)
426 1896	344 1531	254 1130	138 614	100 445	71 316

Notes
 Balls - Carbon Steel Grade 520
 Washers - Carbon Steel Case Hard
 Bands - Carbon Steel Soft
 Bearings Oiled with a Rust Preventative
 All Bearings Marked on Band with "Designation Nice USA" as Shown"

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560342
Diámetro interior	9.53 mm
Diámetro exterior	26.59 mm
Espesor	9.12 mm
Peso	30 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE