

Rodamiento de bolas una hilera 618-V-NICE - 618-V-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/618-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
618™	V	1.375 34.92	1.406 35.93	2.1502 62.71	.625 15.88	23 114	0.45 0.20

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1794 7980	1449 6445	1089 4755	579 2578	419 1884	298 1328

Notes
Balls - Carbon Steel Grade 520
Washers - Carbon Steel Case Hard

Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560502
Diámetro interior	34.92 mm
Diámetro exterior	62.71 mm
Espesor	15.88 mm
Peso	200 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE