


Accesorio de cojinete 7609-DL-NICE - 7609-DL-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/accesorio/7609-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE 7TH DECIMAL
- EASY TO USE INCH DIMENSIONS
- MODERN DESIGN
- PAIR SPEED RATES - 5000 - 8000 RPM
- THROUGH HARDENED
- GRIND HARDEN
- STEEL CASE STAINLESS
- BRONZE BEADED STAINLESS
- EXCELLENT APPROPRIATE ANGLE OF CONTACT
- AVAILABLE SINGLE BEADED OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS WILL ENHANCE LIFE IN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE VIBRATION AND SHOCK ARE REQUIRED.



PRINCIPLE DIMENSIONS

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7609™	.625 14.29	1.750 44.27	0.6250 15.88	0.0625 1.59	1.009 25.63	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.00	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2095 11548	1025 4061	0.34 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3616060473400
Diámetro interior	14.29 mm
Diámetro exterior	25.63 mm
Espesor	15.88 mm
Peso	150 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE